Applicant
 : Satoshi Seo et al.
 Attorney's Docket No.: 12732

 Serial No.: 10/623.609
 087002 / US5381/5474/5502D1

Filed : July 22, 2003 Page : 2 of 19

Amendments to the Claims

This listing of claims replaces all prior versions and listings of claims in the application.

Listing of Claims

1-128. (Canceled)

129. (Currently Amended) A light emitting device comprising:

- a first electrode;
- a second electrode;
- a hole transporting region comprising a hole transporting material adjacent to the first electrode;
- an electron transporting region comprising an electron transporting material adjacent to the second electrode;
- a light emitting region comprising an organic compound the hole transporting material and the electron transporting material interposed between the hole transporting region and the electron transporting region, the light emitting region having a capability of transporting both holes and electrons; and
 - a dopant included only in a portion of the light emitting region.
 - 130. (Currently Amended) A light emitting device comprising:

an anode;

a cathode;

- a hole transporting region comprising a hole transporting material adjacent to the anode;
- an electron transporting region comprising an electron transporting material adjacent to the cathode;
- a light emitting region comprising an organic compound the hole transporting material and the electron transporting material interposed between the hole transporting region and the

Applicant : Satoshi Seo et al. Serial No. : 10/623,609 Filed : July 22, 2003 Page : 3 of 19

electron transporting region, said light emitting region having a capability of transporting both holes and electrons; and

a dopant included only in a portion of the light emitting region.

131. (Currently Amended) A light emitting device comprising:

an anode;

a cathode;

a hole transporting region comprising a hole transporting material adjacent to the first electrode anode;

an electron transporting region comprising an electron transporting material adjacent to the second electrode cathode;

a light emitting region comprising an organic compound the hole transporting material and the electron transporting material interposed between the hole transporting region and the electron transporting region, the light emitting region having a capability of transporting both holes and electrons: and

a dopant included only in a portion of the light emitting region, wherein the dopant is a triplet light emitting material.

132. (Currently Amended) A light emitting device comprising:

an anode:

a cathode;

a hole transporting region comprising a hole transporting material adjacent to the anode; an electron transporting region comprising an electron transporting material adjacent to the cathode:

a light emitting region comprising an organic compound the hole transporting material and the electron transporting material interposed between the hole transporting region and the electron transporting region, said light emitting region having a capability of transporting both holes and electrons; and

Applicant: Satoshi Seo et al. Serial No.: 10/623,609 Filed: July 22, 2003 Page: 4 of 19

> a dopant included only in a portion of the light emitting region, wherein the dopant is a triplet light emitting material, and wherein the light emitting region includes a host to the dopant.

> 133. (Currently Amended) A light emitting device comprising:

a first electrode;

a second electrode;

a hole transporting region comprising a hole transporting material adjacent to the first electrode;

an electron transporting region comprising an electron transporting material adjacent to the second electrode:

a light emitting region comprising an organic compound the hole transporting material and the electron transporting material interposed between the hole transporting region and the electron transporting region, the light emitting region having a capability of transporting both holes and electrons; and

a dopant included only in a central portion of the light emitting region.

134. (Currently Amended) A light emitting device comprising:

an anode;

a cathode:

a hole transporting region comprising a hole transporting material adjacent to the anode; an electron transporting region comprising an electron transporting material adjacent to the cathode:

a light emitting region comprising an organic compound the hole transporting material and the electron transporting material interposed between the hole transporting region and the electron transporting region, said light emitting region having a capability of transporting both holes and electrons; and

a dopant included in only a central portion of the light emitting region.

Applicant: Satoshi Seo et al. Serial No.: 10/623,609 Filed: July 22, 2003 Page: 5 of 19

135. (Currently Amended) A light emitting device comprising:

an anode;

a cathode;

a hole transporting region comprising a hole transporting material adjacent to the anode; an electron transporting region comprising an electron transporting material adjacent to the cathode:

a light emitting region comprising an organic compound the hole transporting material and the electron transporting material interposed between the hole transporting region and the electron transporting region, the light emitting region having a capability of transporting both holes and electrons; and

a dopant included in only a central portion of the light emitting region, wherein the dopant is a triplet light emitting material.

136. (Currently Amended) A light emitting device comprising:

an anode:

a cathode;

a hole transporting region comprising a hole transporting material adjacent to the anode; an electron transporting region comprising an electron transporting material adjacent to the cathode:

a light emitting region comprising an organic compound the hole transporting material and the electron transporting material interposed between the hole transporting region and the electron transporting region, said light emitting region having a capability of transporting both holes and electrons; and

a dopant included in only a central portion of the light emitting region,

wherein the dopant is a triplet light emitting material, and

wherein the light emitting region includes a host to the dopant.

Applicant : Satoshi Seo et al. Serial No. : 10/623,609 Filed : July 22, 2003

Page : 6 of 19

137. (Previously Presented) A light emitting device according to claim 129, wherein at least one of the first electrode and the second electrode is light-transmissive.

- 138. (Previously Presented) A light emitting device according to claim 130, wherein at least one of the anode and the cathode is light-transmissive.
- 139. (Previously Presented) A light emitting device according to claim 129, wherein the light emitting region has a thickness of 30 nm or more.
- 140. (Currently Amended) A light emitting device according to claim 129, wherein the depart is included in a thickness of 10 nm from a interface between the light emitting region and the anode or the eathode the portion of the light emitting region including the dopant has a thickness of 10 to 20 nm, and the portion is apart from an interface between the light emitting region and the hole transporting region or the electron transporting region.
- 141. (Previously Presented) A light emitting device according to claim 129, wherein the light emitting device is an electric apparatus selected from a display device, a video camera, a digital camera, an image reproducing device, a mobile portable computer, a personal computer, a cellular phone, and an audio.
- 142. (Previously Presented) A light emitting device according to claim 130, wherein the light emitting region has a thickness of 30 nm or more.
- 143. (Currently Amended) A light emitting device according to claim 130, wherein the dopant is included in a thickness of 10 nm from an interface between the light emitting region and the hole transporting region or the electron transporting region the portion of the light emitting region including the dopant has a thickness of 10 to 20 nm, and the portion is apart from

Applicant: Satoshi Seo et al. Serial No.: 10/623,609 Filed: July 22, 2003

Page : 7 of 19

an interface between the light emitting region and the hole transporting region or the electron transporting region.

- 144. (Previously Presented) A light emitting device according to claim 130, wherein the light emitting device is an electric apparatus selected from a display device, a video camera, a digital camera, an image reproducing device, a mobile portable computer, a personal computer, a cellular phone, and an audio.
- 145. (Previously Presented) A light emitting device according to claim 131, wherein at least one of the anode and the cathode is light-transmissive.
- 146. (Previously Presented) A light emitting device according to claim 132, wherein at least one of the anode and the cathode is light-transmissive.
- 147. (Previously Presented) A light emitting device according to claim 131, wherein the light emitting region has a thickness of 30 nm or more.
- 148. (Currently Amended) A light emitting device according to claim 131, wherein the dopant is included in a thickness of 10 nm from a interface between the light emitting region and the anode or the cathode the portion of the light emitting region including the dopant has a thickness of 10 to 20 nm, and the portion is apart from an interface between the light emitting region and the hole transporting region or the electron transporting region.
- 149. (Previously Presented) A light emitting device according to claim 131, wherein the light emitting device is an electric apparatus selected from a display device, a video camera, a digital camera, an image reproducing device, a mobile portable computer, a personal computer, a cellular phone, and an audio.

 Applicant
 : Satoshi Seo et al.
 Attorney's Docket No.: 12732

 Serial No.: 10/623,609
 087002 / US5381/5474/5502D1

Filed : July 22, 2003 Page : 8 of 19

150. (Previously Presented) A light emitting device according to claim 132, wherein the light emitting region has a thickness of 30 nm or more.

- 151. (Currently Amended) A light emitting device according to claim 132, wherein the dopant is included in a thickness of 10 nm from a interface between the light emitting region and the hole transporting region or the electron transporting region the portion of the light emitting region including the dopant has a thickness of 10 to 20 nm, and the portion is apart from an interface between the light emitting region and the hole transporting region or the electron transporting region.
- 152. (Previously Presented) A light emitting device according to claim 132, wherein the light emitting device is an electric apparatus selected from a display device, a video camera, a digital camera, an image reproducing device, a mobile portable computer, a personal computer, a cellular phone, and an audio.
- 153. (Previously Presented) A light emitting device according to claim 133, wherein at least one of the first electrode and the second electrode is light-transmissive.
- 154. (Previously Presented) A light emitting device according to claim 134, wherein at least one of the anode and the cathode is light-transmissive.
- 155. (Previously Presented) A light emitting device according to claim 133, wherein the light emitting region has a thickness of 30 nm or more.
- 156. (Currently Amended) A light emitting device according to claim 133, wherein the depart is included in a thickness of 10 nm from a interface between the light emitting region and the anode or the eathode the central portion of the light emitting region including the depart has

Applicant: Satoshi Seo et al. Serial No.: 10/623,609 Filed: July 22, 2003

Page : 9 of 19

a thickness of 10 to 20 nm, and the central portion is apart from an interface between the light emitting region and the hole transporting region or the electron transporting region.

- 157. (Previously Presented) A light emitting device according to claim 133, wherein the light emitting device is an electric apparatus selected from a display device, a video camera, a digital camera, an image reproducing device, a mobile portable computer, a personal computer, a cellular phone, and an audio.
- 158. (Previously Presented) A light emitting device according to claim 134, wherein the light emitting region has a thickness of 30 nm or more.
- 159. (Currently Amended) A light emitting device according to claim 134, wherein the depart is included in a thickness of 10 nm from a interface between the light emitting region and the anode or the eathede the central portion of the light emitting region including the depart has a thickness of 10 to 20 nm, and the central portion is apart from an interface between the light emitting region and the hole transporting region or the electron transporting region.
- 160. (Previously Presented) A light emitting device according to claim 134, wherein the light emitting device is an electric apparatus selected from a display device, a video camera, a digital camera, an image reproducing device, a mobile portable computer, a personal computer, a cellular phone, and an audio.
- 161. (Previously Presented) A light emitting device according to claim 135, wherein at least one of the anode and the cathode is light-transmissive.
- 162. (Previously Presented) A light emitting device according to claim 136, wherein at least one of the anode and the cathode is light-transmissive.

 Applicant
 : Satoshi Seo et al.
 Attorney's Docket No.: 12732

 Serial No.: 10/623.609
 087002 / US5381/5474/5502D1

Filed : July 22, 2003 Page : 10 of 19

Page : 10 01 19

163. (Previously Presented) A light emitting device according to claim 135, wherein the light emitting region has a thickness of 30 nm or more.

- 164. (Currently Amended) A light emitting device according to claim 135, wherein the dopant is included in a thickness of 10 nm from an interface between the light emitting region and the anode or the eathode the central portion of the light emitting region including the dopant has a thickness of 10 to 20 nm, and the central portion is apart from an interface between the light emitting region and the hole transporting region or the electron transporting region.
- 165. (Previously Presented) A light emitting device according to claim 135, wherein the light emitting device is an electric apparatus selected from a display device, a video camera, a digital camera, an image reproducing device, a mobile portable computer, a personal computer, a cellular phone, and an audio.
- 166. (Previously Presented) A light emitting device according to claim 136, wherein the light emitting region has a thickness of 30 nm or more.
- 167. (Currently Amended) A light emitting device according to claim 136, wherein the depart is included in a thickness of 10 nm from a interface between the light emitting region and the hole transporting region or the electron transporting region the central portion of the light emitting region including the dopant has a thickness of 10 to 20 nm, and the central portion is apart from an interface between the light emitting region and the hole transporting region or the electron transporting region.
- 168. (Previously Presented) A light emitting device according to claim 136, wherein the light emitting device is an electric apparatus selected from a display device, a video camera, a digital camera, an image reproducing device, a mobile portable computer, a personal computer, a cellular phone, and an audio.

 Applicant
 : Satoshi Seo et al.
 Attorney's Docket No.: 12732

 Serial No.: 10/623,609
 087002 / US5381/5474/5502D1

Filed : July 22, 2003 Page : 11 of 19

169. (Previously Presented) A light emitting device according to claim 129, wherein the dopant comprises an organic compound.

- 170. (Previously Presented) A light emitting device according to claim 130, wherein the dopant comprises an organic compound.
- 171. (Previously Presented) A light emitting device according to claim 131, wherein the dopant comprises an organic compound.
- 172. (Previously Presented) A light emitting device according to claim 132, wherein the dopant comprises an organic compound.
- 173. (Previously Presented) A light emitting device according to claim 133, wherein the dopant comprises an organic compound.
- 174. (Previously Presented) A light emitting device according to claim 134, wherein the dopant comprises an organic compound.
- 175. (Previously Presented) A light emitting device according to claim 135, wherein the dopant comprises an organic compound.
- 176. (Previously Presented) A light emitting device according to claim 136, wherein the dopant comprises an organic compound.
- 177. (Previously Presented) A light emitting device according to claim 169, wherein the organic compound is at least one selected from the group of tris (2-phenylpyridine) iridium, 2, 3,

Applicant : Satoshi Seo et al. Serial No. : 10/623,609 Filed : July 22, 2003 Page : 12 of 19

7, 8, 12, 13, 17, 18-octaethyl-21H, 23H- porphyrin-platinum, perylene, rubrene, and 4-(dicyanomethylene)-2-methyl-6-(p-dimethylaminostyryl)-4H-pyran.

178. (Previously Presented) A light emitting device according to claim 170, wherein the organic compound is at least one selected from the group of tris (2-phenylpyridine) iridium, 2, 3, 7, 8, 12, 13, 17, 18-octaethyl-21H, 23H-porphyrin-platinum, perylene, rubrene, and 4-(dicyanomethylene)-2-methyl-6-(p-dimethylaminostyryl)-4H-pyran.

179. (Previously Presented) A light emitting device according to claim 171, wherein the organic compound is at least one selected from the group of tris (2-phenylpyridine) iridium, 2, 3, 7, 8, 12, 13, 17, 18-octaethyl-21H, 23H-porphyrin-platinum, perylene, rubrene, and 4-(dicyanomethylene)-2-methyl-6-(p-dimethylaminostyryl)-4H-pyran.

180. (Previously Presented) A light emitting device according to claim 172, wherein the organic compound is at least one selected from the group of tris (2-phenylpyridine) iridium, 2, 3, 7, 8, 12, 13, 17, 18-octaethyl-21H, 23H-porphyrin-platinum, perylene, rubrene, and 4-(dicyanomethylene)-2-methyl-6-(p-dimethylaminostyryl)-4H-pyran.

181. (Previously Presented) A light emitting device according to claim 173, wherein the organic compound is at least one selected from the group of tris (2-phenylpyridine) iridium, 2, 3, 7, 8, 12, 13, 17, 18-octaethyl-21H, 23H-porphyrin-platinum, perylene, rubrene, and 4-(dicyanomethylene)-2-methyl-6-(p-dimethylaminostyryl)-4H-pyran.

182. (Previously Presented) A light emitting device according to claim 174, wherein the organic compound is at least one selected from the group of tris (2-phenylpyridine) iridium, 2, 3, 7, 8, 12, 13, 17, 18-octaethyl-21H, 23H-porphyrin-platinum, perylene, rubrene, and 4-(dicvanomethylene)-2-methyl-6-(p-dimethylaminostyryl)-4H-pyran.

Applicant: Satoshi Seo et al. Serial No.: 10/623,609 Filed: July 22, 2003 Page: 13 of 19

183. (Previously Presented) A light emitting device according to claim 175, wherein the organic compound is at least one selected from the group of tris (2-phenylpyridine) iridium, 2, 3, 7, 8, 12, 13, 17, 18-octaethyl-21H, 23H-porphyrin-platinum, perylene, rubrene, and 4-(dicyanomethylene)-2-methyl-6-(p-dimethylaminostyryl)-4H-pyran.

- 184. (Previously Presented) A light emitting device according to claim 176, wherein the organic compound is at least one selected from the group of tris (2-phenylpyridine) iridium, 2, 3, 7, 8, 12, 13, 17, 18-octaethyl-21H, 23H-porphyrin-platinum, perylene, rubrene, and 4-(dicyanomethylene)-2-methyl-6-(p-dimethylaminostyryl)-4H-pyran.
- 185. (Currently Amended) A light emitting device according to claim [[137]] 129, wherein the hole transporting material is at least one selected from the group of 4, 4"-bis [N-(3-methylphenyl)-N-phenyl-amino]-biphenyl, 4, 4"-tris [N-(1-naphthyl)-N-phenyl-amino]-biphenyl, 4, 4", 4"-tris (N, N-diphenyl-amino)-triphenylamine, and 4, 4", 4"-tris [N-(3-methylphenyl)-N-phenyl-amino]-triphenylamine.
- 186. (Previously Presented) A light emitting device according to claim 130, wherein the hole transporting material is at least one selected from the group of 4, 4'-bis [N-(3-methylphenyl)-N-phenyl-amino]-biphenyl, 4, 4'-bis [N-(1-naphthyl)-N-phenyl-amino]-biphenyl, 4, 4', 4"-tris (N, N-diphenyl-amino)-triphenylamine, and 4, 4', 4"-tris [N-(3-methylphenyl)-N-phenyl-amino]-triphenylamine.
- 187. (Currently Amended) A light emitting device according to claim [[145]] 131, wherein the hole transporting material is at least one selected from the group of 4, 4'-bis [N-(3-methylphenyl)-N-phenyl-amino]-biphenyl, 4, 4'-bis [N-(1-naphthyl)-N-phenyl-amino]-biphenyl, 4, 4', 4"-tris (N, N-diphenyl-amino)-triphenylamine, and 4, 4', 4"-tris [N-(3-methylphenyl)-N-phenyl-amino]-triphenylamine.

Applicant : Satoshi Seo et al. Serial No. : 10/623,609 Filed : July 22, 2003 Page : 14 of 19

188. (Previously Presented) A light emitting device according to claim 132, wherein the hole transporting material is at least one selected from the group of 4, 4'-bis [N-(3-methylphenyl)-N-phenyl-amino]-biphenyl, 4, 4'-bis [N-(1-naphthyl)-N-phenyl-amino]-biphenyl, 4, 4', 4"-tris (N, N-diphenyl-amino)-triphenylamine, and 4, 4', 4"-tris [N-(3-methylphenyl)-N-phenyl-amino]-triphenylamine.

- 189. (Currently Amended) A light emitting device according to claim [[153]] 133, wherein the hole transporting material is at least one selected from the group of 4, 4'-bis [N-(3-methylphenyl)-N-phenyl-amino]-biphenyl, 4, 4'-bis [N-(1-naphthyl)-N-phenyl-amino]-biphenyl, 4, 4', 4"-tris [N, N-diphenyl-amino)-triphenylamine, and 4, 4', 4"-tris [N-(3-methylphenyl)-N-phenyl-amino]-triphenylamine.
- 190. (Previously Presented) A light emitting device according to claim 134, wherein the hole transporting material is at least one selected from the group of 4, 4'-bis [N-(3-methylphenyl)-N-phenyl-amino]-biphenyl, 4, 4'-bis [N-(1-naphthyl)-N-phenyl-amino]-biphenyl, 4, 4', 4"-tris (N, N-diphenyl-amino)-triphenylamine, and 4, 4', 4"-tris [N-(3-methylphenyl)-N-phenyl-amino]-triphenylamine.
- 191. (Currently Amended) A light emitting device according to claim [[161]] 135, wherein the hole transporting material is at least one selected from the group of 4, 4'-bis [N-(3-methylphenyl)-N-phenyl-amino]-biphenyl, 4, 4'-bis [N-(1-naphthyl)-N-phenyl-amino]-biphenyl, 4, 4', 4"-tris (N, N-diphenyl-amino)-triphenylamine, and 4, 4', 4"-tris [N-(3-methylphenyl)-N-phenyl-amino]-triphenylamine.
- 192. (Previously Presented) A light emitting device according to claim 136, wherein the hole transporting material is at least one selected from the group of 4, 4'-bis [N-(3-methylphenyl)-N-phenyl-amino]-biphenyl, 4, 4'-bis [N-(1-naphthyl)-N-phenyl-amino]-biphenyl,

Applicant : Satoshi Seo et al. Serial No. : 10/623,609 Filed : July 22, 2003 Page : 15 of 19

4, 4', 4"-tris [N, N-diphenyl-amino)-triphenylamine, and 4, 4', 4"-tris [N-(3-methylphenyl)-N-phenyl-amino]-triphenylamine.

193. (Currently Amended) A light emitting device according to claim [[138]] 129. wherein the electron transporting material is at least one selected from the group of tris (8-quinolinolato) aluminium, tris (4-methyl-8-quinolinolato) aluminium, bis (10-hydroxybenzo[h]-quinolinato) beryllium, bis (2-methyl-8-quinolinolato)-(4-phenylphenolate)-aluminium, bis [2-(2-hydroxyphenyl)-benzoxazolato] zinc, bis [2-(2-hydroxyphenyl)-benzothiazolato] zinc, 2-(4-biphenylyl)-5-(4-tert-butylphenyl)-1, 3, 4-oxadiazole, 1, 3-bis[5-(p-tert-butylphenyl)-1, 2, 4-triazole, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-(4-ethylphenyl-1, 2, 4-triazole, bathophenanthroline, and bathocuproine.

194. (Previously Presented) A light emitting device according to claim 130, wherein the electron transporting material is at least one selected from the group of tris (8-quinolinolato) aluminium, tris (4-methyl-8-quinolinolato) aluminium, bis (10-hydroxybenzo[h]-quinolinato) beryllium, bis (2-methyl-8-quinolinolato)-(4-phenylphenolate)-aluminium, bis [2-(2-hydroxyphenyl)-benzoxazolato] zinc, bis [2-(2-hydroxyphenyl)-benzothiazolato] zinc, 2-(4-biphenylyl)-5-(4-tert-butylphenyl)-1, 3, 4-oxadiazole, 1, 3-bis[5-(p-tert-butylphenyl)-1, 3, 4-oxadiazole-2-il] benzene, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-(4-ethylphenyl-1, 2, 4-triazole, bathophenanthroline, and bathocuproine.

195. (Currently Amended) A light emitting device according to claim [[146]] 131, wherein the electron transporting material is at least one selected from the group of tris (8-quinolinolato) aluminium, tris (4-methyl-8-quinolinolato) aluminium, bis (10-hydroxybenzo[h]-quinolinato) beryllium, bis (2-methyl-8-quinolinolato)-(4-phenylphenolate)-aluminium, bis [2-(2-hydroxyphenyl)-benzoxazolato] zinc, bis [2-(2-hydroxyphenyl)-benzothiazolato] zinc, 2-(4-

Applicant : Satoshi Seo et al. Serial No. : 10/623,609 Filed : July 22, 2003 Page : 16 of 19

biphenylyl)-5-(4-tert-butylphenyl)-1, 3, 4-oxadiazole, 1, 3-bis[5-(p-tert-butylphenyl)-1, 3, 4-oxadiazole-2-il] benzene, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-phenyl-1, 2, 4-triazole, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-(4-ethylphenyl-1, 2, 4-triazole, bathophenanthroline, and bathocuproine.

196. (Previously Presented) A light emitting device according to claim 132, wherein the electron transporting material is at least one selected from the group of tris (8-quinolinolato) aluminium, tris (4-methyl-8-quinolinolato) aluminium, bis (10-hydroxybenzo[h]-quinolinato) beryllium, bis (2-methyl-8-quinolinolato)-(4-phenylphenolate)-aluminium, bis [2-(2-hydroxyphenyl)-benzoxazolato] zinc, bis [2-(2-hydroxyphenyl)-benzothiazolato] zinc, 2-(4-biphenylyl)-5-(4-tert-butylphenyl)-1, 3, 4-oxadiazole, 1, 3-bis[5-(p-tert-butylphenyl)-1, 2, 4-triazole, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-(4-ethylphenyl-1, 2, 4-triazole, bathophenanthroline, and bathocuproine.

197. (Currently Amended) A light emitting device according to claim [[154]] 133. wherein the electron transporting material is at least one selected from the group of tris (8-quinolinolato) aluminium, tris (4-methyl-8-quinolinolato) aluminium, bis (10-hydroxybenzo[h]-quinolinato) beryllium, bis (2-methyl-8-quinolinolato)-(4-phenylphenolate)-aluminium, bis [2-(2-hydroxyphenyl)-benzoxazolato] zinc, bis [2-(2-hydroxyphenyl)-benzothiazolato] zinc, 2-(4-biphenylyl)-5-(4-tert-butylphenyl)-1, 3, 4-oxadiazole, 1, 3-bis[5-(p-tert-butylphenyl)-1, 3, 4-oxadiazole-2-il] benzene, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-(4-ethylphenyl-1, 2, 4-triazole, bathophenanthroline, and bathocuproine.

198. (Previously Presented) A light emitting device according to claim 134, wherein the electron transporting material is at least one selected from the group of tris (8-quinolinolato) aluminium, tris (4-methyl-8-quinolinolato) aluminium, bis (10-hydroxybenzo[h]-quinolinato)

 Applicant : Satoshi Seo et al.
 Attorney's Docket No.: 12732

 Serial No.: 10/623,609
 087002 / US5381/5474/5502D1

Filed : July 22, 2003 Page : 17 of 19

beryllium, bis (2-methyl-8-quinolinolato)-(4-phenylphenolate)-aluminium, bis [2-(2-hydroxyphenyl)-benzoxazolato] zinc, bis [2-(2-hydroxyphenyl)-benzothiazolato] zinc, 2-(4-biphenylyl)-5-(4-tert-butylphenyl)-1, 3, 4-oxadiazole, 1, 3-bis[5-(p-tert-butylphenyl)-1, 3, 4-oxadiazole-2-il] benzene, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-phenyl-1, 2, 4-triazole, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-(4-ethylphenyl-1, 2, 4-triazole, bathophenanthroline, and bathocuproine.

199. (Currently Amended) A light emitting device according to claim [[162]] 135, wherein the electron transporting material is at least one selected from the group of tris (8-quinolinolato) aluminium, tris (4-methyl-8-quinolinolato) aluminium, bis (10-hydroxybenzo[h]-quinolinato) beryllium, bis (2-methyl-8-quinolinolato)-(4-phenylphenolate)-aluminium, bis [2-(2-hydroxyphenyl)-benzoxazolato] zinc, bis [2-(2-hydroxyphenyl)-benzothiazolato] zinc, 2-(4-biphenylyl)-5-(4-tert-butylphenyl)-1, 3, 4-oxadiazole, 1, 3-bis[5-(p-tert-butylphenyl)-1, 3, 4-oxadiazole-2-il] benzene, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-phenyl-1, 2, 4-triazole, bathophenanthroline, and bathocuproine.

200. (Previously Presented) A light emitting device according to claim 136, wherein the electron transporting material is at least one selected from the group of tris (8-quinolinolato) aluminium, tris (4-methyl-8-quinolinolato) aluminium, bis (10-hydroxybenzo[h]-quinolinato) beryllium, bis (2-methyl-8-quinolinolato)-(4-phenylphenolate)-aluminium, bis [2-(2-hydroxyphenyl)-benzoxazolato] zinc, bis [2-(2-hydroxyphenyl)-benzothiazolato] zinc, 2-(4-biphenylyl)-5-(4-tert-butylphenyl)-1, 3, 4-oxadiazole, 1, 3-bis[5-(p-tert-butylphenyl)-1, 3, 4-oxadiazole-2-il] benzene, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-phenyl-1, 2, 4-triazole, 5-(4-biphenylyl)-3-(4-tert-butylphenyl)-4-(4-ethylphenyl-1, 2, 4-triazole, bathophenanthroline, and bathocuproine.